

PREPARE TO BE FLOORED.

Pitmaster - Hickory Traditional



Lightly brushed and smoked hickory.

The surface is lightly brushed to allow for a uniform darkening of the wood with a light smoked appearance. Usually straight grained, but occasionally wavy or irregular, hickory has a somewhat coarse texture. Hickory is a very strong wood that, if treated well, will last a lifetime with minimal wear.

Flooring/Paneling

Great on walls and ceilings, perfect for floors!

Random Widths	3"-5", 3"-6", 4"-6", 4"-8"
Specified Widths	3"-8"
Thickness	3/4", 5/8", or 1/2"
Lengths	2-12' Random or Specified Lengths
Milled Profile	Tongue and Groove, Square or Shiplap
Surface Texture	Brushed
Edges	Square or Pillowed
Recommended Finish	UV Oil
Optional Finish	Hardwax Oil

Stair Treads and Parts

We'll glue, sand and cut to size to your design specifications, and shape your treads with a variety of edges.

Wood Tops

Countertops, table tops, and bar tops all shaped to suit with a variety of edges.

Thickness	1 1/2"
Edges	Eased or Milled Profile
Recommended Finish	Hardwax Oil
Optional Finish	Commercial



Elmwood Reclaimed Timber

22701 S. Peculiar Drive

Peculiar, Missouri 64078

elmwoodreclaimedtimber.com

(800) 705-0705 toll free

(816) 779-7300 phone

(816) 779-7307 fax