

PREPARE TO BE FLOORED.

Rock Salt - Hickory Traditional



Brushed Hickory with a white tones.

The surface is lightly brushed in order to accept the white oil that tones down some of the natural variation in the wood. Usually straight grained, but occasionally wavy or irregular, hickory has a somewhat coarse texture. Hickory is a very strong wood that, if treated well, will last a lifetime with minimal wear.

Flooring/Paneling

Great on walls and ceilings, perfect for floors!

Random Widths	3"-5", 3"-6", 4"-6", 4"-8"
Specified Widths	3"-8"
Thickness	3/4", 5/8", or 1/2"
Lengths	2-12' Random or Specified Lengths
Milled Profile	Tongue and Groove, Square or Shiplap
Surface Texture	Brushed
Edges	Square or Pillowed
Recommended Finish	UV Oil
Optional Finish	Hardwax Oil

Stair Treads and Parts

We'll glue, sand and cut to size to your design specifications, and shape your treads with a variety of edges.

Wood Tops

Countertops, table tops, and bar tops all shaped to suit with a variety of edges.

Thickness	1 1/2"
Edges	Eased or Milled Profile
Finish	Hardwax Oil



Elmwood Reclaimed Timber

22701 S. Peculiar Drive

Peculiar, Missouri 64078

elmwoodreclaimedtimber.com

(800) 705-0705 toll free

(816) 779-7300 phone

(816) 779-7307 fax

PREPARE TO BE FLOORED.



Elmwood Reclaimed Timber
22701 S. Peculiar Drive
Peculiar, Missouri 64078
elmwoodreclaimedtimber.com

(800) 705-0705 toll free
(816) 779-7300 phone
(816) 779-7307 fax